

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

AMENDMENTS TO THE CLAIMS

1 1. (Currently Amended) A support attachment for mounting work implements on a
2 ladder, the ladder including a pair of upwardly extending substantially parallel side rails spaced
3 from each other and steps extending horizontally between said side rails to enable a person to
4 climb the ladder, said side rails each having opposed ~~front and rear~~ first and second surfaces, said
5 support attachment comprising:
6 a ~~pair of parallel spacer~~ configured to extend ~~arms for extending~~ across and of a breadth
7 to non-rotatably rest resting on the step of the ladder;
8 [a] side rail engaging means extending from said ~~pair of parallel spacer arms~~ for engaging
9 the ~~rear~~ first surface of the side rails of the ladder above the step engaged by said step engaging
10 means;
11 a support structure for supporting work implements, said support structure mounted to
12 and extending from said ~~pair of parallel spacer arms for supporting said support structure at the~~
13 ~~front surfaces of~~ in a direction away from said side rails engaging means and configured for
14 placement adjacent the second surface of said side rails of the ladder; and
15 said spacer being of a breadth sufficient to non-rotatably secure said support attachment
16 to the step of the ladder; and
17 ~~wherein~~ said side rail engaging means and said support structure ~~are being~~ rigidly
18 connected to said pair of parallel spacer arms.

D1
Contd

Serial No.: 09/876,688
Group Art Unit: 3632

1 2. (Previously Amended) The support attachment for a ladder as described in claim 1,
2 wherein:
3 said support structure for supporting work implements comprises a U-shaped
4 frame including parallel spaced side legs and a base leg extending between said side legs,
5 said base leg joined to said pair of parallel spacer arms, and
6 a rectilinear spool support rod having opposed ends is releasably mounted to said side
7 legs of said U-shaped frame;
8 whereby spools of wire can be rotatably mounted on said spool support rod at the front of
9 the side rails of the ladder.

1 3. (Previously Amended) The support attachment of claim 2, wherein said U-shaped frame,
2 said pair of parallel spacer arms and said side rail engaging means are of one piece construction.

1 4. (Original) The support attachment of claim 1, wherein:
2 said side rail engaging means comprises a rectilinear bar having opposed ends;
3 said step engaging means comprises a pair of substantially parallel bars extending
4 from said rectilinear bar to said support structure, and
5 said support structure comprises a U-shaped frame having a base leg with opposed end
6 portions, a pair of parallel side legs extending from the end portions of said base leg, and said
7 base leg connected intermediate its end portions to said parallel bars of said step engaging
8 means; and

DI
contd

Serial No.: 09/876,688
Group Art Unit: 3632

9 a rectilinear spool support rod having opposed ends supported by said parallel side legs of
10 said support structure.

1 5. (Previously Amended) The support attachment of claim 4, wherein said pair of parallel
2 spacer arms, said side rail engaging means and said support structure occupy a common plane.

1 6. (Cancelled).

1 7. (Previously Amended) The support structure of claim 1, wherein said pair of parallel
2 spacer arms, said side rail engaging means and said support structure define oppositely facing C-
3 shaped recesses which register about the side rails of the step ladder.

1 8. (Previously Amended) The support structure of claim 1, wherein said pair of parallel
2 spacer arms comprises a pair of substantially parallel spaced apart bars extending from said side
3 rail engaging means for resting at spaced intervals on the step of the step ladder whereby said
4 pair of parallel spacer arms maintains said support structure in a fixed attitude with respect to the
5 step of the ladder on which said pair of parallel spacer arms rests.

1 9. (Currently Amended) A method for storing and dispensing spools of electrical wire on a
2 wire caddy with the wire caddy mounted on a step ladder having parallel upwardly extending
3 side rails and a step extending horizontally between the side rails, wherein said wire caddy is
4 comprised of a support bar connected to a pair of parallel spacer bars, said spacer bars further

5 connected to a base leg having ~~two parallel legs configured~~ at distal ends thereof and a spool
6 support rod ~~positioned~~ extending between said parallel legs, comprising the steps of:
7 positioning the support bar on one side of the upwardly extending side rails of the ladder,
8 positioning the base leg on the other side of the upwardly extending side rails of the
9 ladder,
10 ~~positioning said wire caddy on a ladder wherein said pair of parallel spacer bars~~
11 ~~rests~~ resting the spacer bars upon a ~~the~~ step of said ladder;
12 maintaining said wire caddy in a fixed, non-rotatable position by the engagement of said
13 pair of parallel spacer bars on the step of the ladder;
14 suspending said spool support rod between said distal ends of said parallel legs;
15 securing said spool support rod to said distal end of each of said parallel legs with a
16 suitable fastening means; and
17 mounting spools of wire onto said spool support rod such that said spools of wire project
18 outwardly from said ladder.

1 10. (Cancelled).

1 11. (Previously Amended) The method of claim 9, further comprising the step of configuring
2 said support bar, pair of spacer bars and base leg of said wire caddy so as to form oppositely
3 facing C-shaped recesses, each for registering about a side rail of the ladder, and engaging each
4 of the oppositely facing C-shaped recesses about a side rail of the ladder.

D
contd

1 12. (Original) The method of claim 9, wherein the spool support rod is suspended between
2 said parallel legs by positioning said spool support rod through openings in said distal ends of
3 said parallel legs.

1 13. (Previously Amended) The method of claim 9, wherein said securing step further
2 includes positioning locking pins in opposing ends of said spool support rod.

1 14. (Currently Amended) The method of claim 9, wherein mounting said spools of wire ~~are~~
2 ~~mounted-onto~~ said spool support rod ~~comprising-comprises~~ the steps of:
3 removing one end of said spool support rod from a secured position at the distal end of
4 one of the parallel legs, disengaging said fastening means and sliding said spool support rod
5 through an opening in said distal end of one of said parallel legs;
6 threading said spooled wire onto said spool support rod; and
7 securing said spool support rod back into position between said parallel legs.

1 15. (Currently Amended) A wire caddy attachable to a ladder, the ladder having parallel
2 upwardly extending side rails and horizontal steps extending between said side rails, said wire
3 caddy comprising:
4 a U-shaped frame having a base leg and opposed parallel legs mounted to said base leg
5 for placement on one side of the steps of the ladder;
6 a spool support rod supported at its ends by said parallel legs for supporting a spool of
7 wire;

DI
contd

Serial No.: 09/876,688
Group Art Unit: 3632

8 a support bar extending parallel to said base leg of said U-shaped frame for placement on
9 the other side of the steps of the ladder;
10 a pair of spacer bars rigidly interconnecting said U-shaped frame to said support bar for
11 extending across a step of the ladder and spaced from each other a distance sufficient to balance
12 said U-shaped frame on the ladder when wire is paid out from the spool of wire; and
13 said U-shaped frame, said support bar and said pair of spacer bars formed in a common
14 plane,
15 whereby said pair of spacer bars engages the step of a ladder and said support bar is
16 positioned on one side of the side rails of the ladder and said U-shaped frame is positioned on the
17 other side of the side rails of the ladder, and said pair of spacer bars maintains said wire caddy in
18 a fixed, non-rotatable position on the ladder, a spool of wire is mounted on the spool support rod,
19 and wire is paid out from the spool of wire.

1 16. (Original) The wire caddy of claim 15, wherein the U-shaped frame is of rigid
2 construction and has sufficient strength to support said wire caddy when fully-loaded with
3 spooled wire.

1 17. (Original) The wire caddy of claim 15, wherein said spool support rod is secured
2 between said parallel legs such that it does not inadvertently detach from said U-shaped frame
3 during use.

Diad
Amended

1 18. (Currently amended) The wire caddy of claim 17, ~~further comprising spools of wire~~
2 ~~threaded onto said spool support rod such that said~~ wherein the spools of wire are ~~free to rotate~~
3 rotatable about said spool support rod ~~during use~~.

1 19. (Currently Amended) The wire caddy of claim 15, wherein said spacer bars extending
2 from the support bar to said U-shaped frame extend parallel to each other and are sized and
3 spaced from each other to ~~rest~~ balance said caddy upon a step of the ladder.

1 20. (Currently Amended) The wire caddy of claim 19, further comprising said spacer bars
2 constructed and arranged so that when said spacer bars are placed on the step of the ladder said
3 spool support rod is oriented horizontally ~~and a spooled wire projects outwardly from said~~
4 ~~ladder~~.

1 21. (Currently Amended) The wire caddy of claim 15, wherein each end of said support bar
2 is constructed and arranged so that the ends of the support bar engage a rear surface of a side rail
3 of said ladder at a position ~~directly~~ above a step engaged by said spacer bars.

1 22. (Previously Amended) The wire caddy of claim 15, wherein said spacer bars are
2 intermediately positioned from each distal end of said support bar and said base leg so as to
3 define oppositely facing c-shaped recesses for engagement about a pair of side rails of the ladder.

1 23. (Cancelled).
